

Datum: 26.05.2026

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



Reducerna objemka 240, N.N./N.N.Rp 1 1/4Rp 1

Kategorija: [Socket 240, reducing, female/female](#)
Šifra: **113036RIE**

(slika je simbolična)

Kratek opis

Bushing 240, reducing, IT/IT, Rp 1 1/4, Rp 1, Operating temp. -20°C to 300°C, black malleable cast iron, Hot-dip galvanised

Acc. to DIN EN 10242 (formerly DIN 2950)

The classic - and the most popular - screw fitting series for pipe construction.

These fittings are characterized by their high mechanical strength and surface quality to DIN 2444.

They are completely coated with a layer of pure zinc and are therefore suitable for drinking water

Tehnične Specifikacije

| | |
|--------------------------------|---|
| Min. temperaturno območje [°C] | -20 |
| Material | Black malleable iron B350-10, design symbol A |
| Navoj 1 | Rp 1 1/4 |
| Navoj 2 | Rp 1 |
| Površina | Hot dip galvanised |
| Standardni navoj | acc. ISO 7-1 |
| Max. temperaturno območje [°C] | 300 |