**TRG d.o.o.**
**Celovška cesta 150, 1000 Ljubljana**

**Davčna št.:** SI 56119488
**Telefon:** 01 500 14 42
**E-mail:** info@podjetje-trg.si
**WWW:** www.www.karcher-trg.si

**Datum:** 24.11.2026



(slika je simbolična)

# Reducerna objemka 240, Rp 1 1/4 N.N.Rp 1 N.N.

Kategorija: Socket 240, reducing, female/female, black
Šifra: **133706RIE**

## Kratek opis

Bushing 240, reducing, IT/IT, Rp 1 1/4, Rp 1, black malleable iron fitting, Operating temp. -20 °C to 300 °C, ISO 7-1
According to DIN EN 10242 (previously 2950).
Malleable iron cast fittings in black steel, non-galvanized, is the classic fitting series in connection series in piping construction. Our malleable iron cast fittings are characterized by high mechanical strength and standardized fitting technology.
Working minimal temperature = -20 °C, 25 bar.
Working pressure for temperature range from -20 °C to 120 °C: 25 bar.
Working pressure for temperature range from 120 °C to 300 °C: 20-25 bar.

## Tehnične Specifikacije

| | |
|---|---|
| Min. temperaturno območje [°C] | -20 |
| Material | Black malleable iron B350-10, design symbol A |
| Navoj 1 | Rp 1 1/4 |
| Navoj 2 | Rp 1 |
| Površina | Black |
| Standardni navoj | acc. ISO 7-1 |
| Max. temperaturno območje [°C] | 300 |