TRG d.o.o.
Celovška cesta 150, 1000 Ljubljana

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.www.karcher-trg.si

Datum: 24.11.2026



(slika je simbolična)

Reducerna objemka 240, Rp 3/4 N.N.Rp 3/8 N.N.

Kategorija: Socket 240, reducing, female/female, black
Šifra: **133699RIE**

Kratek opis

Bushing 240, reducing, IT/IT, Rp 3/4, Rp 3/8, black malleable iron fitting, Operating temp. -20 °C to 300 °C, ISO 7-1
According to DIN EN 10242 (previously 2950).
Malleable iron cast fittings in black steel, non-galvanized, is the classic fitting series in connection series in piping construction. Our malleable iron cast fittings are characterized by high mechanical strength and standardized fitting technology.
Working minimal temperature = -20 °C, 25 bar.
Working pressure for temperature range from -20 °C to 120 °C: 25 bar.
Working pressure for temperature range from 120 °C to 300 °C: 20-25 bar.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Material	Black malleable iron B350-10, design symbol A
Navoj 1	Rp 3/4
Navoj 2	Rp 3/8
Površina	Black
Standardni navoj	acc. ISO 7-1
Max. temperaturno območje [°C]	300