

Datum: 06.06.2026

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

Reducirni nastavek 241,R 3/4 Z.N.Rp 1/4 N.N.

Kategorija: [Reducing bush 241, male/female, black](#)
Šifra: **133730RIE**

Kratek opis

Reducing piece 241, R 3/4 ET, Rp 1/4 IT black malleable iron fitting, operating temp. -20 °C to 300 °C, ISO 7-1 According to DIN EN 10242 (previously 2950). Malleable iron cast fittings in black steel, non-galvanized, is the classic fitting series in connection series in piping construction. Our malleable iron cast fittings are characterized by high mechanical strength and standardized fitting technology.
Working minimal temperature = -20 °C, 25 bar.
Working pressure for temperature range from -20 °C to 120 °C: 25 bar.
Working pressure for temperature range from 120 °C to 300 °C: 20-25 bar.

Tehnične Specifikacije

| | |
|--------------------------------|---|
| Min. temperaturno območje [°C] | -20 |
| Material | Black malleable iron B350-10, design symbol A |
| Navoj 1 | R 3/4 |
| Navoj 2 | Rp 1/4 |
| Površina | Black |
| Standardni navoj | acc. ISO 7-1 |
| Max. temperaturno območje [°C] | 300 |