



(slika je simbolična)

## [Serv. enota 2-delna »FUTURA«PC Vel.2,G1/2, 0.5-10, Pol avto.](#)

Kategorija: [Service unit, 2-piece with PC bowl and bowl guard](#)  
Šifra: **139554RIE**

### Kratek opis

Service unit 2-part »FUTURA« with PC container, Protective cage and pressure gauge, Size 2, G 1/2, Control range 0.5-10 bar, Semi  
Two-piece service units with excellent flow rates in modern design.  
Lockable diaphragm pressure regulator with secondary ventilation, oil can be filled without interrupting operation.

### Tehnične Specifikacije

|                                |   |
|--------------------------------|---|
| Min. temperaturno območje [°C] | -10   |
| Element filtra Membrane        | Cellpor (PE)<br>NBR   |
| Merjenje pretoka               | At $P_1 = 10$ bar, $P_2 = 6.3$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj                          | G 1/2   |
| Odtok kondenzata               | Semi-automatic  |
| Ohišje                         | PA66 GF60   |
| Posoda                         | Polycarbonate container with protective cage                            |
| Priključni navoj               | Material: Die-cast zinc   |
| Serijska                       | FUTURA  |
| Srednje                        | Compressed air, neutral gases   |
| Tesnilo                        | NBR   |
| Vidna kupola                   | PC  |
| Min. krmilno območje [bar]     | 0.5   |
| Min. vhodni tlak [bar]         | 1.5   |
| Velikost                       | 2   |
| Rang filtra [ $\mu$ m]         | 5   |
| Max. krmilno območje [bar]     | 10  |
| Max. vhodni tlak [bar]         | 16  |
| Zaslon manometra max. [bar]    | 16  |
| Max. temperaturno območje [°C] | 50  |
| C [mm]                         | 110.0   |
| A [mm]                         | 126.0   |
| B [mm]                         | 257.0   |
| Pretok [l/min]                 | 3500  |