

Datum: 04.07.2025



(slika je simbolična)

## [Serv. enota 2-delna »FUTURA« PC Vel.2,G3/8, 0.5-10, Pol avto.](#)

Kategorija: [Service unit, 2-piece with PC bowl and bowl guard](#)  
Šifra: **139549RIE**

### Kratek opis

Service unit 2-part »FUTURA« with PC container, Protective cage and pressure gauge, Size 2, G 3/8, Control range 0.5-10 bar, Semi  
Two-piece service units with excellent flow rates in modern design.  
Lockable diaphragm pressure regulator with secondary ventilation, oil can be filled without interrupting operation.

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Element filtra Membrane	Cellpor (PE) NBR
Merjenje pretoka	At $P_1 = 10$ bar, $P_2 = 6.3$ bar and pressure drop $\Delta_p = 1$ bar
Navoj	G 3/8
Odtok kondenzata	Semi-automatic
Ohišje	PA66 GF60
Posoda	Polycarbonate container with protective cage
Priključni navoj	Material: Die-cast zinc
Serijska	FUTURA
Srednje	Compressed air, neutral gases
Tesnilo	NBR
Vidna kupola	PC
Min. krmilno območje [bar]	0.5
Min. vhodni tlak [bar]	1.5
Velikost	2
Rang filtra [ $\mu$ m]	5
Max. krmilno območje [bar]	10
Max. vhodni tlak [bar]	16
Zaslon manometra max. [bar]	16
Max. temperaturno območje [°C]	50
C [mm]	110.0
A [mm]	126.0
B [mm]	257.0
Pretok [l/min]	3500