



(slika je simbolična)

Serv. enota 2-delna »G«Kov. pos.5 µmVel. 600G 3/4

Kategorija: [Service unit, 2-piece with metal bowl, sight glass](#)Šifra: **116382RIE**

Kratek opis

Service unit 2-part »G«, Metal container, Viewing tube, 5 µm, Size 600, G 3/4, Input pressure max. 10 bar, Control range 1.5-9 bar
Two-piece service units consisting of a diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

Tehnične Specifikacije

| | |
|------------------------------|--|
| Merjenje pretoka | At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj | G 3/4 |
| Odtok kondenzata | Semi-automatic |
| Ohišje | Die-cast aluminium |
| Posoda | Metal container with viewing tube |
| Serija | G |
| Tesnilo | NBR |
| Vidna kupola | Brass/POM |
| Vzmet pokrova motorja | POM |
| Min. krmilno območje [bar] | 1.5 |
| Rang filtra [µm] | 5 |
| Max. krmilno območje [bar] | 9 |
| Max. vhodni tlak [bar] | 10 |
| Max. sobna temperatura [°C] | 70 |
| Max. temperatura medija [°C] | 70 |
| C [mm] | 144.0 |
| A [mm] | 190.0 |
| D [mm] | 219.0 |
| B [mm] | 363.0 |
| Velikost | 600 |
| Pretok [l/min] | 4200 |