



(slika je simbolična)

## Serv. enota 2-delna »G«PC zbir.5 µmVel. 300G 3/8

Kategorija: [Service unit, 2-piece with PC bowl, bowl guard](#)Šifra: **116375RIE**

### Kratek opis

Service unit 2-part »G«, PC container, Protective cage, 5 µm, Size 300, G 3/8, Input pressure max. 10 bar, Control range 1.5-9 bar  
Two-piece service units consisting of a diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

### Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Navoj	G 3/8
Odtok kondenzata	Fully-automatic
Ohišje	Die-cast aluminium
Posoda	Polycarbonate container with protective cage
Serija	G
Tesnilo	NBR
Vidna kupola	Brass/POM
Vzmet pokrova motorja	POM
Min. krmilno območje [bar]	1.5
Rang filtra [µm]	5
Max. krmilno območje [bar]	9
Max. vhodni tlak [bar]	10
Max. sobna temperatura [°C]	70
Max. temperatura medija [°C]	70
C [mm]	82.5
A [mm]	115.0
D [mm]	143.0
B [mm]	225.5
Velikost	300
Pretok [l/min]	1350