

Datum: 06.03.2026

Serv. enota 2-delna »GA« Kov. pos.5 µm, Vel. 600, G 1

Kategorija: [Service unit, 2-piece with metal bowl, sight glass](#)
Šifra: **178504RIE**

(slika je simbolična)

Kratek opis

Service unit 2-part »GA«, Metal container, Viewing tube, 5 µm, Size 600, G 1, Input pressure max. 10 bar, Control range 1.5-9 bar

Two-piece service units consisting of a diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-5
Merjenje pretoka	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Navoj	G 1
Odtok kondenzata	Fully-automatic
Ohišje	Die-cast aluminium
Posoda	Metal container with viewing tube
Serijska	GA
Tesnilo	NBR
Vidna kupola	Brass/POM
Vzmet pokrova motorja	POM
Min. krmilno območje [bar]	1.5
Rang filtra [µm]	5
Max. krmilno območje [bar]	9
Max. vhodni tlak [bar]	10
Max. temperaturno območje [°C]	70
C [mm]	131.5
D [mm]	205.0
A [mm]	206.0
B [mm]	336.5
Velikost	600
Pretok [l/min]	6000