



Serv. enota 2-delna »GA« PC zbir.5 µm, Vel. 300, G 1/2

Kategorija: [Service unit, 2-piece with PC bowl, bowl guard](#)
Šifra: **178493RIE**

(slika je simbolična)

Kratek opis

Service unit 2-part »GA«, PC container, Protective cage, 5 µm, Size 300, G1/2, Input pressure max. 10 bar, Control range 1.5-9 bar

Two-piece service units consisting of a diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

Tehnične Specifikacije

| | |
|--------------------------------|--|
| Min. temperaturno območje [°C] | -5 |
| Merjenje pretoka | At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj | G 1/2 |
| Odtok kondenzata | Semi-automatic |
| Ohišje | Die-cast aluminium |
| Posoda | Polycarbonate container with protective cage |
| Serijska | GA |
| Tesnilo | NBR |
| Vidna kupola | Brass/POM |
| Vzmet pokrova motorja | POM |
| Min. krmilno območje [bar] | 1.5 |
| Rang filtra [µm] | 5 |
| Max. krmilno območje [bar] | 9 |
| Max. vhodni tlak [bar] | 10 |
| Max. temperaturno območje [°C] | 70 |
| C [mm] | 89.0 |
| A [mm] | 128.5 |
| D [mm] | 158.0 |
| B [mm] | 247.0 |
| Velikost | 300 |
| Pretok [l/min] | 2000 |