



(slika je simbolična)

Serv. enota 2-delna »Stinard« Zašč. kletka Vel.2,G 3/8

Kategorija: [Service unit, 2-piece with PC bowl and bowl guard](#)
Šifra: **101054RIE**

Kratek opis

Service unit 2-part »Standard«, PC container, protective cage, Size 2, G 3/8, Input pressure max. 16 bar, Control range 0.5-10 bar
Two-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

Tehnične Specifikacije

| | |
|------------------------------|--|
| Merjenje pretoka | At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar |
| Navoj | G 3/8 |
| Odtok kondenzata | Semi-automatic |
| Ohišje | Die-cast zinc / aluminium, painted silver |
| Posoda | Polycarbonate container with protective cage |
| Serija | Standard |
| Tesnilo | NBR |
| Vidna kupola | PA |
| Min. krmilno območje [bar] | 0.5 |
| Velikost DN | 10 |
| Max. krmilno območje [bar] | 10 |
| Max. vhodni tlak [bar] | 16 |
| Zaslon manometra max. [bar] | 16 |
| Rang filtra [μ m] | 40 |
| Max. sobna temperatura [°C] | 60 |
| Max. temperatura medija [°C] | 60 |
| Manometer \varnothing [mm] | 63 |
| C [mm] | 120.5 |
| A [mm] | 150.0 |
| B [mm] | 266.4 |
| Pretok [l/min] | 800 |