



(slika je simbolična)

## Serv. enota 2-delna »Stinard« Zašč. kletka Vel.2,G 3/8

Kategorija: [Service unit, 2-piece with PC bowl and bowl guard](#)  
Šifra: **101054RIE**

### Kratek opis

Service unit 2-part »Standard«, PC container, protective cage, Size 2, G 3/8, Input pressure max. 16 bar, Control range 0.5-10 bar  
Two-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

### Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar
Navoj	G 3/8
Odtok kondenzata	Semi-automatic
Ohišje	Die-cast zinc / aluminium, painted silver
Posoda	Polycarbonate container with protective cage
Serija	Standard
Tesnilo	NBR
Vidna kupola	PA
Min. krmilno območje [bar]	0.5
Velikost DN	10
Max. krmilno območje [bar]	10
Max. vhodni tlak [bar]	16
Zaslon manometra max. [bar]	16
Rang filtra [ $\mu$ m]	40
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
Manometer $\varnothing$ [mm]	63
C [mm]	120.5
A [mm]	150.0
B [mm]	266.4
Pretok [l/min]	800