



(slika je simbolična)

## Serv. enota 2-delna »Stinard« Zašč. kletka Vel.4, G 3/4

Kategorija: [Service unit, 2-piece with PC bowl and bowl guard](#)  
Šifra: **101056RIE**

### Kratek opis

Service unit 2-part »Standard«, PC container, protective cage, Size 4, G 3/4, Input pressure max. 16 bar, Control range 0.5-10 bar  
Two-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

### Tehnične Specifikacije

|                              |  |
|------------------------------|--|
| Merjenje pretoka             | At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar |
| Navoj                        | G 3/4  |
| Odtok kondenzata             | Semi-automatic   |
| Ohišje                       | Die-cast zinc / aluminium, painted silver                            |
| Posoda                       | Polycarbonate container with protective cage                         |
| Serija                       | Standard   |
| Tesnilo                      | NBR  |
| Vidna kupola                 | PA   |
| Min. krmilno območje [bar]   | 0.5  |
| Velikost                     | 4  |
| Max. krmilno območje [bar]   | 10   |
| Max. vhodni tlak [bar]       | 16   |
| Zaslona manometra max. [bar] | 16   |
| DN                           | 20   |
| Rang filtra [ $\mu$ m]       | 40   |
| Max. sobna temperatura [°C]  | 60   |
| Max. temperatura medija [°C] | 60   |
| Manometer $\varnothing$ [mm] | 63   |
| C [mm]                       | 190.6  |
| A [mm]                       | 220.0  |
| B [mm]                       | 452.0  |
| Pretok [l/min]               | 4000   |