



(slika je simbolična)

[Serv. enota 2-delna »variobloc«Kov. pos.Vel. 2G 3/4](#)

Kategorija: [Service unit, 2-piece with metal bowl, sight glass](#)Šifra: **125348RIE**

Kratek opis

Service unit 2-part »variobloc«, Metal container incl. viewing tube and metal drip cap, Size 2, G 3/4, Input pressure max. 20 bar

Two-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

Approved series in modern industrial design, with the following key benefits:

- Simple handling
- Convenient modular assembly thanks to innovative fasteners
- Excellent flow values

Tehnične Specifikacije

| | |
|------------------------------|---|
| Membrane | NBR |
| Merjenje pretoka | At $P_1 = 10$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj | G 3/4 |
| Odtok kondenzata | Manual |
| Ohišje | Die-cast zinc |
| Posoda | Metal container with viewing tube |
| Serija | variobloc |
| Tesnilo | NBR |
| Vidna kupola | PA |
| Vzmet pokrova motorja | POM |
| Min. krmilno območje [bar] | 0.5 |
| Velikost | 2 |
| Max. krmilno območje [bar] | 10 |
| Zaslon manometra max. [bar] | 10 |
| Max. vhodni tlak [bar] | 20 |
| Rang filtra [μ m] | 40 |
| Max. sobna temperatura [°C] | 80 |
| Max. temperatura medija [°C] | 80 |
| C [mm] | 98.0 |
| A [mm] | 140.0 |
| B [mm] | 273.0 |
| Pretok [l/min] | 5000 |