



(slika je simbolična)

## Serv. enota 3-delna»FUTURA« Kov. Vel.1, G 1/4, 0.5-8 Avt.

Kategorija: [Service unit, 3-piece with metal bowl, sight glass](#)  
Šifra: **152690RIE**

### Kratek opis

Service unit 3-part »FUTURA« with metal container, Viewing tube and pressure gauge, Size 1, G 1/4, Control range 0.5-8 bar, Fully  
Three-piece service units with excellent flow rates in modern design.  
Lockable diaphragm pressure regulator with secondary ventilation, oil can be filled without interrupting operation.

### Tehnične Specifikacije

|                                |  |
|--------------------------------|--|
| Min. temperaturno območje [°C] | -10  |
| Element filtra Membrane        | Cellpor (PE)<br>NBR<br>At $P_1 = 10$ bar, $P_2 = 6.3$ bar and pressure drop $\Delta_p = 1$ bar |
| Merjenje pretoka               | G 1/4  |
| Navoj                          | Fully-automatic  |
| Odtok kondenzata               | PA66 GF60  |
| Ohišje                         | Metal container with viewing tube  |
| Posoda                         | Material: Die-cast zinc  |
| Priključni navoj               | FUTURA   |
| Serijska                       | Compressed air, neutral gases  |
| Srednje                        | NBR  |
| Tesnilo                        | PC   |
| Vidna kupola                   | PC   |
| Min. krmilno območje [bar]     | 0.5  |
| Velikost                       | 1  |
| Min. vhodni tlak [bar]         | 1.5  |
| Rang filtra [µm]               | 5  |
| Max. krmilno območje [bar]     | 8  |
| Zaslon manometra max. [bar]    | 10   |
| Max. vhodni tlak [bar]         | 16   |
| Max. temperaturno območje [°C] | 50   |
| C [mm]                         | 96.0   |
| A [mm]                         | 156.0  |
| B [mm]                         | 243.0  |
| Pretok [l/min]                 | 1750   |