

## Serv. enota 3-delna »FUTURA« PC, Vel.1, G 3/8, 0.5-16 Avt.

Kategorija: [Service unit, 3-piece with PC bowl and bowl guard](#)  
Šifra: **152642RIE**



(slika je simbolična)

### Kratek opis

Service unit 3-part »FUTURA« with PC container, Protective cage and pressure gauge, Size 1, G 3/8, Control range 0.5-16 bar, Fully  
Three-piece service units with excellent flow rates in modern design.  
Lockable diaphragm pressure regulator with secondary ventilation, oil can be filled without interrupting operation.

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Element filtra Membrane	Cellpor (PE) NBR
Merjenje pretoka	At $P_1 = 10$ bar, $P_2 = 6.3$ bar and pressure drop $\Delta_p = 1$ bar
Navoj	G 3/8
Odtok kondenzata	Fully-automatic
Ohišje	PA66 GF60
Posoda	Polycarbonate container with protective cage
Priključni navoj	Material: Die-cast zinc
Serijska	FUTURA
Srednje	Compressed air, neutral gases
Tesnilo	NBR
Vidna kupola	PC
Min. krmilno območje [bar]	0.5
Velikost	1
Min. vhodni tlak [bar]	1.5
Rang filtra [ $\mu$ m]	5
Max. krmilno območje [bar]	16
Max. vhodni tlak [bar]	16
Zaslona manometra max. [bar]	25
Max. temperaturno območje [°C]	50
C [mm]	96.0
A [mm]	156.0
B [mm]	243.0
Pretok [l/min]	1750