

## Serv. enota 3-delna »FUTURA« PC, Vel.2, G 3/8, 0.5-10 Avt.

Kategorija: [Service unit, 3-piece with PC bowl and bowl guard](#)  
Šifra: **152646RIE**



(slika je simbolična)

### Kratek opis

Service unit 3-part »FUTURA« with PC container, Protective cage and pressure gauge, Size 2, G 3/8, Control range 0.5-10 bar, Fully  
Three-piece service units with excellent flow rates in modern design.  
Lockable diaphragm pressure regulator with secondary ventilation, oil can be filled without interrupting operation.

### Tehnične Specifikacije

|                                |   |
|--------------------------------|---|
| Min. temperaturno območje [°C] | -10   |
| Element filtra Membrane        | Cellpor (PE)<br>NBR   |
| Merjenje pretoka               | At $P_1 = 10$ bar, $P_2 = 6.3$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj                          | G 3/8   |
| Odtok kondenzata               | Fully-automatic   |
| Ohišje                         | PA66 GF60   |
| Posoda                         | Polycarbonate container with protective cage                            |
| Priključni navoj               | Material: Die-cast zinc   |
| Serijska                       | FUTURA  |
| Srednje                        | Compressed air, neutral gases   |
| Tesnilo                        | NBR   |
| Vidna kupola                   | PC  |
| Min. krmilno območje [bar]     | 0.5   |
| Min. vhodni tlak [bar]         | 1.5   |
| Velikost                       | 2   |
| Rang filtra [ $\mu$ m]         | 5   |
| Max. krmilno območje [bar]     | 10  |
| Max. vhodni tlak [bar]         | 16  |
| Zaslon manometra max. [bar]    | 16  |
| Max. temperaturno območje [°C] | 50  |
| C [mm]                         | 110.0   |
| A [mm]                         | 189.0   |
| B [mm]                         | 273.0   |
| Pretok [l/min]                 | 3500  |