



(slika je simbolična)

## Serv. enota 3-delna »FUTURA« PC, Vel.4, G 3/4, 0.5-16 Avt.

Kategorija: [Service unit, 3-piece with PC bowl and bowl guard](#)  
Šifra: **152657RIE**

### Kratek opis

Service unit 3-part »FUTURA« with PC container, Protective cage and pressure gauge, Size 4, G 3/4, Control range 0.5-16 bar, Fully

Three-piece service units with excellent flow rates in modern design.

Lockable diaphragm pressure regulator with secondary ventilation, oil can be filled without interrupting operation.

### Tehnične Specifikacije

|                                |   |
|--------------------------------|---|
| Min. temperaturno območje [°C] | -10   |
| Element filtra Membrane        | Cellpor (PE)<br>NBR   |
| Merjenje pretoka               | At $P_1 = 10$ bar, $P_2 = 6.3$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj                          | G 3/4   |
| Odtok kondenzata               | Fully-automatic   |
| Ohišje                         | PA66 GF60   |
| Poraba zraka                   | Yes   |
| Posoda                         | Polycarbonate container with protective cage                            |
| Priključni navoj               | Material: Die-cast zinc   |
| Serija                         | FUTURA  |
| Srednje                        | Compressed air, neutral gases   |
| Tesnilo                        | NBR   |
| Vidna kupola                   | PC  |
| Min. krmilno območje [bar]     | 0.5   |
| Max. notranja poraba zraka     | 1.5 l/min (depending on secondary pressure)                             |
| Min. vhodni tlak [bar]         | 1.5   |
| Velikost                       | 4   |
| Rang filtra [µm]               | 5   |
| Max. krmilno območje [bar]     | 16  |
| Max. vhodni tlak [bar]         | 16  |
| Zaslon manometra max. [bar]    | 25  |
| Max. temperaturno območje [°C] | 50  |
| C [mm]                         | 137.0   |
| A [mm]                         | 255.0   |
| B [mm]                         | 343.0   |
| Pretok [l/min]                 | 12000   |