

Datum: 14.03.2026



(slika je simbolična)

## [Serv. enota 3-delna »G«Kov. pos.5 µmVel. 600G 1](#)

Kategorija: [Service unit, 3-piece with metal bowl, sight glass](#)  
Šifra: **116430RIE**

### Kratek opis

Service unit 3-part »G«, Metal container, Viewing tube, 5 µm, Size 600, G 1, Input pressure max. 10 bar, Control range 1.5-9 bar

Three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, centrifugal separator and proportional lubricator.

### Tehnične Specifikacije

|                              |  |
|------------------------------|--|
| Merjenje pretoka             | At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj                        | G 1  |
| Odtok kondenzata             | Fully-automatic  |
| Ohišje                       | Die-cast aluminium   |
| Posoda                       | Metal container with viewing tube                                    |
| Serija                       | G  |
| Tesnilo                      | NBR  |
| Vidna kupola                 | Brass/POM  |
| Vzmet pokrova motorja        | POM  |
| Min. krmilno območje [bar]   | 1.5  |
| Rang filtra [µm]             | 5  |
| Max. krmilno območje [bar]   | 9  |
| Max. vhodni tlak [bar]       | 10   |
| C [mm]                       | 61.5   |
| Max. sobna temperatura [°C]  | 70   |
| Max. temperatura medija [°C] | 70   |
| D [mm]                       | 219.0  |
| B [mm]                       | 280.5  |
| A [mm]                       | 295.0  |
| Velikost                     | 600  |
| Pretok [l/min]               | 3750   |