



(slika je simbolična)

[Serv. enota 3-delna »G«Kov. pos.5 µmVel. 600G 1](#)

Kategorija: [Service unit, 3-piece with metal bowl, sight glass](#)
Šifra: **116430RIE**

Kratek opis

Service unit 3-part »G«, Metal container, Viewing tube, 5 µm, Size 600, G 1, Input pressure max. 10 bar, Control range 1.5-9 bar

Three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, centrifugal separator and proportional lubricator.

Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Navoj	G 1
Odtok kondenzata	Fully-automatic
Ohišje	Die-cast aluminium
Posoda	Metal container with viewing tube
Serija	G
Tesnilo	NBR
Vidna kupola	Brass/POM
Vzmet pokrova motorja	POM
Min. krmilno območje [bar]	1.5
Rang filtra [µm]	5
Max. krmilno območje [bar]	9
Max. vhodni tlak [bar]	10
C [mm]	61.5
Max. sobna temperatura [°C]	70
Max. temperatura medija [°C]	70
D [mm]	219.0
B [mm]	280.5
A [mm]	295.0
Velikost	600
Pretok [l/min]	3750