

Datum: 23.03.2026



(slika je simbolična)

Serv. enota 3-delna »GA« Kov. pos.5 µm, Vel. 600, G 1

Kategorija: [Service unit, 3-piece with metal bowl, sight glass](#)
Šifra: **178516RIE**

Kratek opis

Service unit 3-part »GA«, Metal container, Viewing tube, 5 µm, Size 600, G 1, Input pressure max. 10 bar, Control range 1.5-9 bar

Three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, centrifugal separator and proportional lubricator.

Tehnične Specifikacije

| | |
|--------------------------------|--|
| Min. temperaturno območje [°C] | -5 |
| Merjenje pretoka | At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj | G 1 |
| Odtok kondenzata | Semi-automatic |
| Ohišje | Die-cast aluminium |
| Posoda | Metal container with viewing tube |
| Serija | GA |
| Tesnilo | NBR |
| Vidna kupola | Brass/POM |
| Vzmet pokrova motorja | POM |
| Min. krmilno območje [bar] | 1.5 |
| Rang filtra [µm] | 5 |
| Max. krmilno območje [bar] | 9 |
| Max. vhodni tlak [bar] | 10 |
| C [mm] | 62.5 |
| Max. temperaturno območje [°C] | 70 |
| D [mm] | 205.0 |
| B [mm] | 267.5 |
| A [mm] | 312.0 |
| Velikost | 600 |
| Pretok [l/min] | 4800 |