

Datum: 02.07.2026



(slika je simbolična)

## [Serv. enota 3-delna »GA« Kov. pos.5 µm, Vel. 600, G 3/4](#)

Kategorija: [Service unit, 3-piece with metal bowl, sight glass](#)  
Šifra: **178515RIE**

### Kratek opis

Service unit 3-part »GA«, Metal container, Viewing tube, 5 µm, Size 600, G3/4, Input pressure max. 10 bar, Control range 1.5-9 bar

Three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, centrifugal separator and proportional lubricator.

### Tehnične Specifikacije

|                                |  |
|--------------------------------|--|
| Min. temperaturno območje [°C] | -5   |
| Merjenje pretoka               | At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj                          | G 3/4  |
| Odtok kondenzata               | Semi-automatic   |
| Ohišje                         | Die-cast aluminium   |
| Posoda                         | Metal container with viewing tube                                    |
| Serija                         | GA   |
| Tesnilo                        | NBR  |
| Vidna kupola                   | Brass/POM  |
| Vzmet pokrova motorja          | POM  |
| Min. krmilno območje [bar]     | 1.5  |
| Rang filtra [µm]               | 5  |
| Max. krmilno območje [bar]     | 9  |
| Max. vhodni tlak [bar]         | 10   |
| C [mm]                         | 62.5   |
| Max. temperaturno območje [°C] | 70   |
| D [mm]                         | 205.0  |
| B [mm]                         | 267.5  |
| A [mm]                         | 312.0  |
| Velikost                       | 600  |
| Pretok [l/min]                 | 4800   |