



(slika je simbolična)

## [Serv. enota 3-delna »GA« PC zbir.5 µm, Vel. 400, G 3/8](#)

Kategorija: [Service unit, 3-piece with PC bowl, bowl guard](#)  
Šifra: **178513RIE**

### Kratek opis

Service unit 3-part »GA«, PC container, Protective cage, 5 µm, Size 400, G3/8, Input pressure max. 10 bar, Control range 1.5-9 bar

Three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, centrifugal separator and proportional lubricator.

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-5
Merjenje pretoka	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Navoj	G 3/8
Odtok kondenzata	Fully-automatic
Ohišje	Die-cast aluminium
Posoda	Polycarbonate container with protective cage
Serija	GA
Tesnilo	NBR
Vidna kupola	Brass/POM
Vzmet pokrova motorja	POM
Min. krmilno območje [bar]	1.5
Rang filtra [µm]	5
Max. krmilno območje [bar]	9
Max. vhodni tlak [bar]	10
C [mm]	49.5
Max. temperaturno območje [°C]	70
D [mm]	177.5
B [mm]	227.0
A [mm]	248.0
Velikost	400
Pretok [l/min]	3500