

Datum: 26.06.2026

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si

(slika je simbolična)

Serv. enota 3-delna »multifix«Kov. pos.Vel.4,G 3/4

Kategorija: [Service unit, 3-piece with metal bowl, sight glass](#)Šifra: **133129RIE**

Kratek opis

Service unit 3-part »multifix«, Metal container, Viewing tube, Size 4, G 3/4, Input pressure max. 20 bar, Control range 0.5-10 bar
Three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, centrifugal separator and proportional lubricator.

Tehnične Specifikacije

| | |
|------------------------------|---|
| Merjenje pretoka | At $P_1 = 10$ bar, $P_2 = 6,3$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj | G 3/4 |
| Odtok kondenzata | Semi-automatic |
| Ohišje | Die-cast aluminium |
| Poraba zraka | Yes |
| Posoda | Metal container with viewing tube |
| Serija | multifix |
| Tesnilo | NBR |
| Vidna kupola | Zinc-glass-NBR |
| Vzmet pokrova motorja | POM-brass |
| Min. krmilno območje [bar] | 0.5 |
| Velikost | 4 |
| Rang filtra [μ m] | 5 |
| Max. krmilno območje [bar] | 10 |
| Zaslon manometra max. [bar] | 16 |
| DN | 20 |
| Max. vhodni tlak [bar] | 20 |
| Max. sobna temperatura [°C] | 60 |
| Max. temperatura medija [°C] | 60 |
| C [mm] | 125.0 |
| D [mm] | 190.0 |
| A [mm] | 255.0 |
| B [mm] | 315.0 |
| Pretok [l/min] | 12000 |