



(slika je simbolična)

Serv. enota 3-delna »multifix-mali«PC zbir.Vel. 0G 1/4

Kategorija: [Service unit, 3-piece with polycarbonate bowl](#)
Šifra: **100399RIE**

Kratek opis

Service unit 3-part »multifix-mini« with PC container, Size 0, G 1/4, Input pressure max. 12 bar, Control range 0.5 - 10 bar
Three-piece service units consisting of a diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

Tehnične Specifikacije

| | |
|------------------------------|---|
| Merjenje pretoka | At $P_1 = 10$ bar, $P_2 = 6.3$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj | G 1/4 |
| Odtok kondenzata | Semi-automatic |
| Ohišje | Die-cast zinc |
| Posoda | Polycarbonate container |
| Serija | multifix-mini |
| Tesnilo | NBR |
| Vidna kupola | PA |
| Vzmet pokrova motorja | POM-brass |
| Min. krmilno območje [bar] | 0.5 |
| DN | 5 |
| Rang filtra [μ m] | 5 |
| Max. krmilno območje [bar] | 10 |
| Max. vhodni tlak [bar] | 12 |
| Zaslon manometra max. [bar] | 16 |
| Max. sobna temperatura [°C] | 60 |
| Max. temperatura medija [°C] | 60 |
| C [mm] | 63.0 |
| D [mm] | 102.5 |
| A [mm] | 120.0 |
| B [mm] | 165.5 |
| Pretok [l/min] | 750 |