



(slika je simbolična)

## Serv. enota 3-delna »Stinard«Kov. pos.Vel. 4G 1 1/2

Kategorija: [Service unit, 3-piece with metal bowl](#)  
Šifra: **101087RIE**

### Kratek opis

Service unit 3-part »Standard«, Metal container, metal drip cap, Size 4, G 1 1/2, Input press. max. 25 bar, Control ra. 0.5-16 bar

Three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, centrifugal separator and proportional lubricator.

### Tehnične Specifikacije

|                              |  |
|------------------------------|--|
| Merjenje pretoka             | At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj                        | G 1 1/2  |
| Odtok kondenzata             | Manuel   |
| Ohišje                       | Die-cast zinc / aluminium, painted silver                            |
| Posoda                       | Metal container  |
| Serija                       | Standard   |
| Tesnilo                      | NBR  |
| Vidna kupola                 | Zinc-glass-NBR   |
| Min. krmilno območje [bar]   | 0.5  |
| Velikost                     | 4  |
| Max. krmilno območje [bar]   | 16   |
| Max. vhodni tlak [bar]       | 25   |
| Zaslon manometra max. [bar]  | 25   |
| DN                           | 35   |
| Rang filtra [ $\mu$ m]       | 40   |
| Max. sobna temperatura [°C]  | 60   |
| Max. temperatura medija [°C] | 60   |
| Manometer $\varnothing$ [mm] | 63   |
| C [mm]                       | 70.0   |
| B [mm]                       | 316.0  |
| A [mm]                       | 395.0  |
| Pretok [l/min]               | 5000   |