

Datum: 02.04.2026



(slika je simbolična)

Serv. enota 3-delna »Stinard« z PC zbir.Vel.2,G 3/8

Kategorija: [Service unit, 3-piece with polycarbonate bowl](#)
Šifra: **101066RIE**

Kratek opis

Service unit 3-part »Standard« with polycarbonate container, Size 2, G 3/8, Input pressure max. 16 bar, Control range 0.5 - 10 bar

Three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, centrifugal separator and proportional lubricator.

Tehnične Specifikacije

| | |
|------------------------------|--|
| Merjenje pretoka | At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj | G 3/8 |
| Odtok kondenzata | Semi-automatic |
| Ohišje | Die-cast zinc / aluminium, painted silver |
| Posoda | Polycarbonate container |
| Serijska | Standard |
| Tesnilo | NBR |
| Vidna kupola | PA |
| Min. krmilno območje [bar] | 0.5 |
| Velikost DN | 2 / 6 |
| Max. krmilno območje [bar] | 10 |
| Max. vhodni tlak [bar] | 16 |
| Zaslon manometra max. [bar] | 16 |
| Rang filtra [μ m] | 40 |
| Manometer \varnothing [mm] | 50 |
| C [mm] | 51.0 |
| Max. sobna temperatura [°C] | 60 |
| Max. temperatura medija [°C] | 60 |
| B [mm] | 196.7 |
| A [mm] | 232.0 |
| Pretok [l/min] | 1400 |