

Datum: 25.05.2026



## Serv. enota 3-delna »variobloc« Zašč. kletka Vel. 2G 3/4

Kategorija: [Service unit, 3-piece with PC bowl and bowl guard](#)Šifra: **124860RIE**

(slika je simbolična)

### Kratek opis

Service unit 3-part »variobloc«, PC container and protective cage, Size 2, G 3/4, Input pressure max. 16 bar, Temp. max. 50 °C

Three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator. Approved series in modern industrial design, with the following key benefits:

- Simple handling
- Convenient modular assembly thanks to innovative fasteners
- Excellent flow values

### Tehnične Specifikacije

|                              |  |
|------------------------------|--|
| Membrane                     | NBR  |
| Merjenje pretoka             | At $P_1 = 10$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar            |
| Navoj                        | G 3/4  |
| Odtok kondenzata             | Manual   |
| Ohišje                       | Die-cast zinc<br>Polycarbonate<br>container with<br>protective cage<br>variobloc |
| Posoda                       |  |
| Serija                       | NBR  |
| Tesnilo                      | PA   |
| Vidna kupola                 | POM  |
| Vzmet pokrova motorja        | 0.5  |
| Min. krmilno območje [bar]   | 2  |
| Velikost                     | 10   |
| Max. krmilno območje [bar]   | 10   |
| Zaslon manometra max. [bar]  | 10   |
| Max. vhodni tlak [bar]       | 16   |
| Rang filtra [ $\mu$ m]       | 40   |
| Max. sobna temperatura [°C]  | 50   |
| Max. temperatura medija [°C] | 50   |
| C [mm]                       | 98.0   |
| A [mm]                       | 210.0  |
| B [mm]                       | 274.0  |
| Pretok [l/min]               | 5000   |