



## Serv. enota 3-delna »variobloc« Zašč. kletka Vel.1,G 3/8

Kategorija: [Service unit, 3-piece with PC bowl and bowl guard](#)  
Šifra: **124856RIE**

(slika je simbolična)

### Kratek opis

Service unit 3-part »variobloc«, PC container and protective cage, Size 1, G 3/8, Input pressure max. 16 bar, Temp. max. 50 °C

Three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator. Approved series in modern industrial design, with the following key benefits:

- Simple handling
- Convenient modular assembly thanks to innovative fasteners
- Excellent flow values

### Tehnične Specifikacije

|                              |   |
|------------------------------|---|
| Membrane                     | NBR   |
| Merjenje pretoka             | At $P_1 = 10$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj                        | G 3/8   |
| Odtok kondenzata             | Manual  |
| Ohišje                       | Die-cast zinc Polycarbonate container with protective cage variobloc  |
| Posoda                       |   |
| Serija                       | NBR   |
| Tesnilo                      | PA  |
| Vidna kupola                 | POM   |
| Vzmet pokrova motorja        | 0.5   |
| Min. krmilno območje [bar]   | 1   |
| Velikost                     | 10  |
| Max. krmilno območje [bar]   | 10  |
| Zaslon manometra max. [bar]  | 10  |
| Max. vhodni tlak [bar]       | 16  |
| Rang filtra [ $\mu$ m]       | 40  |
| Max. sobna temperatura [°C]  | 50  |
| Max. temperatura medija [°C] | 50  |
| C [mm]                       | 68.0  |
| A [mm]                       | 144.0   |
| B [mm]                       | 201.0   |
| Pretok [l/min]               | 1800  |