

Service unit 3-part »Standard« with PC container, Size 2, G 3/8

Kategorija: [Service unit, 3-piece with polycarbonate bowl](#)
Šifra: **206302RIE**

(slika je simbolična)

Kratek opis

Service unit 3-part »Standard« with polycarbonate container, Size 2, G 3/8, Input pressure max. 16 bar, Control range 0.5 - 10 bar
Three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, centrifugal separator and proportional lubricator.

Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar
Navoj	G 3/8
Odtok kondenzata	Semi-automatic Die-cast zinc / aluminium, painted silver
Ohišje	Polycarbonate container
Posoda	Standard
Serija	NBR
Tesnilo	PA
Vidna kupola	PA
Min. krmilno območje [bar]	0.5
Velikost	2
Rang filtra [μ m]	5
DN	6
Max. krmilno območje [bar]	10
Max. vhodni tlak [bar]	16
Zaslón manometra max. [bar]	16
Manometer \varnothing [mm]	50
C [mm]	51.0
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
B [mm]	196.7
A [mm]	232.0
Pretok [l/min]	1400