

Datum: 30.03.2026



## Sesalna šalčka meh, Okr. 2.5 pregib, Material NBR, FG Ø 12 mm

Kategorija: [Bellows suction pad, round, 2.5 folds, NBR](#)  
Šifra: **108516RIE**

(slika je simbolična)

### Kratek opis

Bellows suction cup, Round 2.5 folds, Material NBR, »FG«, suitable connection nipple IT G 1/8, ET M5 / G 1/8, Ø12mm  
Robust and hard-wearing suction pad with a single sealing lip.

Used wherever objects (parts, packing materials, etc.) need to be lifted, transported, turned over or handled in some other manner. It is also ideal when it is necessary to compensate varying workpiece heights or uneven surfaces or to handle easily damaged parts. It acts as the connecting element between the vacuum generator and the workpiece.

Properties:

- Soft, flexible folds
- Soft, tapered sealing lips
- Supports on the bottom
- High suction force
- Optimum damping effect
- Very good adaptation to curved workpiece surfaces or materials with uneven surfaces

Applications:

- Handling workpieces with extremely uneven surfaces (e.g. pipes)
- Handling easily damaged parts

### Tehnične Specifikacije

Primerna povezava priključka z notranjim navojem	M5 / G 1/8
Primerna povezava priključka z zunanjim navojem	G 1/8
Prostornina [cm <sup>3</sup> ]	0.600
Sesalna sila [N]	0.9
Izvlačna sila [N]	3.5
Ø notranje cevi [mm]	4
Premer [mm]	12
Min. izbočen polmer krivine [mm]	13
Višina priključka z notranjim navojem [mm]	26.0 / 27.0
Višina priključka z zunanjim navojem [mm]	33.0