

Datum: 19.04.2026



Skozi razdelilno omarico vhod/prehod G 3/4, priključek 1 x G 1/2

Kategorija: [Through distributor with through-hole thread, PN 15](#)
Šifra: **112622RIE**

(slika je simbolična)

Kratek opis

Through distributor, Input/Output G 3/4, Connection 1 x G 1/2, operat.pressure (air/water) max.15 bar, ambient temp. 1 °C to 50 °C

Made of plastic PA6 GF 30.

End and through distributor sockets made of high strength, glass fibre reinforced plastic (PA6 GF 30) with large range of applications.

Optionally 1 or up to 3 connection options as well as 2 thread sizes for internal and external threads (cannot be combined). For vertical carrying of media.

Universal distributor socket with up to 5 connection options. Suitable for vertical and/or horizontal carrying of media or the secure connection

(avoidance of existing components) of pressure reducer or maintenance device, for example.

All distributor sockets have a durable brass threaded insert, whose shape secures it against rotation and against axial shift due to its shape.

Suitable for media compressed air (ambient temperature -10 °C to 50 °C) or water (ambient temperature 1 °C to 50 °C). Drilling diagram dimensions

are identical for all distributor sockets, so a simpler and more flexible exchange between end, through and universal distributor sockets is ensured.

Caution:

Note that the distributor sockets should not be installed in danger zones. Danger zones are, for example, transport routes, escape routes, etc.

Tehnične Specifikacije

| | |
|---|--|
| Dovodni navoj | G 3/4 |
| Navoj skozi luknjo | G 3/4 |
| Ohišje | Glass fibre-reinforced plastic PA6 GF 30 |
| Min. temperaturno območje [°C] | 1 |
| Priključni navoj | 1 x G 1/2 |
| Max. moment privijanja - pritrdilne luknje [Nm] | 4 |
| Max. moment privijanja - medeninasta nit [Nm] | 12 |
| Max. obratovalni tlak [bar] | 15 |
| Max. temperaturno območje [°C] | 50 |