

Datum: 02.07.2026

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

Spir. cev jekl. , PU, cevi Ø 8x5, dolžina 3,0 m

Kategorija: [Spiral hose coupling set with steel coupling](#)
Šifra: **158198RIE**

Kratek opis

Spiral hose coupling set, Steel coupling I.D. 7.8, PU, Hose Ø 8x5, PN at 23 °C max. 12 bar, Length 3.0 m

These exceptionally elastic polyurethane hoses boast a recoil force similar to that of conventional polyamide spiral hose, but with less tendency to loop and significantly better resistance to abrasion.

There is consequently less danger of scratching coated or sensitive surfaces.

The hose is extremely flexible and non-kinking.

Not suitable for direct attachment to pulsating tools.

We recommend using our vibration dampers, according to ISO 6150 § 7.1.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Storitev dolžina max. [m]	3.0
Velikost cevi [mm]	8x5
Max. obratovalni tlak pri 23 ° C [bar]	12
Število tuljav	29
O.D. tuljave [mm]	42
Max. delovna temperatura [°C]	60