TRG d.o.o.
Celovška cesta 150, 1000 Ljubljana

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.www.karcher-trg.si

Datum: 08.11.2026



(slika je simbolična)

spiralna cev spojko, PUR, cev Ø 10x6.5, dolžina 6,0 m

Kategorija: Spiral hose, quick disconnect couplings
Šifra: **113482RIE**

Kratek opis

Spiral hose coupling set I.D. 7.6, PUR, Medium / ambient temperature -20 °C to 60 °C, Hose Ø 10x6.5, PN max. 10 bar, Length 6 m
Spiral or straight polyurethane hose, completely assembled with DN 7.6 safety coupling and steel plugs.
Coupling
Safety coupling made of steel / nickel-plated brass for high flow rates, specially designed for all applications susceptible to severe mechanical wear.
Strong, impact and vibration-resistant design for demanding environments.
Polyurethane hose
Extremely flexible spiral hose with excellent kink resistance and insensitive to dirt.
Combines high tear, tensile and impact strength with a long service life and optimal ageing qualities.
This hose is additionally characterised by outstanding resistance to abrasion and resistance to UV.
Not suitable for direct attachment to pulsating tools.
We recommend using our vibration dampers, according to ISO 6150 § 7.1.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Material	Polyurethane (PUR)
Storitev dolžina max. [m]	6.0
Max. obratovalni tlak [bar]	10
Velikost cevi [mm]	10x6.5
Premer tuljave [mm]	52
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60