TRG d.o.o.
Celovška cesta 150, 1000 Ljubljana

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.www.karcher-trg.si

Datum: 27.11.2026



(slika je simbolična)

spiralna cev vlakni ojačana, PUR, G 3/8, cevi Ø 12x8, 6 m

Kategorija: Spiral hose, swivel adapter and kink protector
Šifra: **113471RIE**

Kratek opis

Spiral hose, Fitting, Kink protection spring, Fibre reinforced, PU, G 3/8, Hose Ø 12x8, PN at 23 °C max. 14 bar, Length 6 m
Standard type or with braided reinforcements for high pressures.
These exceptionally elastic polyurethane hoses boast a recoil force similar to that of conventional nylon spiral hose, but with less tendency to loop and significantly better resistance to abrasion.
There is consequently less danger of scratching coated or sensitive surfaces.
The hose is extremely flexible and non-kinking.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-40
Navoj	G 3/8
Storitev dolžina max. [m]	6.0
Velikost cevi [mm]	12x8
Max. obratovalni tlak pri 23 ° C [bar]	14
O.D. tuljave [mm]	55
Max. delovna temperatura [°C]	74