

Datum: 03.05.2026

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)

(slika je simbolična)

## [Spojka s cevnim nastavkom I.D. 7.6 /Med.pocinkano,Fi 10](#)

Kategorija: [Safety coupling DN 7.6, with hose stem](#)  
Šifra: **107598RIE**

### Kratek opis

Safety coupling I.D. 7.6, Steel / brass galv., Sleeve I.D. 10,  
Operating pressure max. 16 bar, Med./ambient temp. -20 °C  
to 100 °C

"

High-quality, robust and durable, one-hand quick disconnect  
safety couplings, with very high flow rates and only a small  
pressure drop.

The coupling is released fully automatically in two steps. Air  
is relieved from the coupling before it is completely  
disconnected. The plug is only disconnected from the  
coupling if the residual pressure has dropped below 0.3 bar.  
The dreaded "whiplash effect" is thus avoided and the risk  
of injury virtually eliminated.

This safety version conforms to ISO-Standard DIN EN ISO  
4414.

These safety couplings are not suitable for direct  
attachment to pulsating tools.

We recommend using our vibration dampers, according to  
ISO 6150 § 7.1.

Areas of application: Pneumatic system, machine and plant  
engineering, manufacturing industry, workshops,  
automotive, mining.

"

### Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Material	Steel / zinc-plated brass
Merjenje pretoka	at 6 bar and $\Delta_p = 0.5$ bar
Povezava	I.D. 10
Tesnilo	NBR
Vzmet	Stainless steel
DN	7.6
Max. obratovalni tlak [bar]	16
Dolžina [mm]	70.0
Max. sobna temperatura [°C]	100
Max. temperatura medija [°C]	100
Pretok	2250 l/min (air)