



(slika je simbolična)

## Spojka z N.N. I.D. 7.8SEK tip, poniklj. Med.G 3/8 N.N.

Kategorija: [Safety coupling DN 7.8, female](#)  
Šifra: **107534RIE**

### Kratek opis

Safety coupling I.D. 7.8, SEK type, nickel-plated brass, G 3/8 IT, Operating pressure 0 - 35 bar, Temp. -10 °C to 60 °C  
One-hand safety coupling with double locking mechanism.  
Connection: Similar to standard couplings, simply by pressing the plug into the coupling. Disconnection: The first locking mechanism is accessible when the sleeve is pushed back. The coupling valve closes. Air can then be relieved from the plug side (hose). The second locking mechanism is released by actuating the unlocking sleeve again. The coupling can now be disconnected.

### Tehnične Specifikacije

Min. sobna temperatura [°C]	-10
Min. temperatura medija [°C]	-10
Delovni tlak	0 to 35 bar, maximum static working pressure (non-pulsating)
Krogla	Stainless steel
Merjenje pretoka	at 6 bar and $\Delta p = 0.5$ bar
Ohišje	Nickel-plated brass
Povezava	G 3/8 IT
Rokav	Nickel-plated brass
Telo ventila	Nickel-plated brass
Tesnilo	NBR
Vzmet	Stainless steel
DN	7.8
a/f [mm]	22
Dolžina [mm]	46.0
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
Pretok	1100 l/min (air)