

Datum: 04.05.2026

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



## Spojka za varjenje 16, neprekinjen navoj, Rp 2, Dolžina 56 mm

Kategorija: [Weld-on sleeve 16, steel with a bare metal surface](#)  
Šifra: **113292RIE**

(slika je simbolična)

### Kratek opis

Weld-on coupler 16, Steel with a bare metal surface ST 37-2, Continuous thread, Rp 2, Length 56 mm, Working pressure max. 50 bar  
The steel fittings are made of tubular steel to DIN 2441 and boast good resistance to mechanical stresses.  
Hot dip galvanised steel fittings are completely coated with a layer of pure zinc and are therefore protected against rust.  
They are used in pipe construction, plumbing and gas installations as well as a wide range of industrial applications, especially in conjunction with the popular malleable iron series.

### Tehnične Specifikacije

Material	Steel with a bare metal surface ST 37-2
Navoj	Rp 2
Površina	Steel with a bare metal surface
Standardni navoj	acc. ISO 7-1
Max. delovni tlak [bar]	50
Dolžina [mm]	56.0