

Datum: 26.06.2026

stand. cilindrdelujoč v dveh smerehbat Ø 50, hod 500, G 1/4

Kategorija: [Standard cylinders »SAI« Series](#)
Šifra: **170622RIE**

(slika je simbolična)

Kratek opis

Standard cylinder SAI, ISO 15552, double-acting, Piston Ø 50, Stroke 500, G 1/4, Working pressure 1.5-10 bar, Temp. -20°C to 70°C

These cylinders are ideal for a wide range of applications owing to their robust design and excellent value for money. The standard type has a double-acting cylinder and features a magnetic piston as well as integrated cushioning. The magnetic switches are mounted in T-slots on two sides of the body.

Suitable for filtered, unlubricated or lubricated compressed air.

If lubrication is used, it must be continuous.

Tehnične Specifikacije

| | |
|--------------------------------|--|
| Min. temperaturno območje [°C] | -20 |
| Bat | Aluminium |
| Batnica | Steel, thick-chromed |
| Cushioning | cushioned |
| ET batnice | M16x1.5 |
| Ffunkcija | double-acting |
| Gewinde Kolbenstange | male piston rod |
| Magnet | with magnet |
| Ovoj | Aluminium jacket with integrated T-slots |
| Povezava | G 1/4 |
| Standard | acc. to ISO 15552 |
| Tesnilo | NBR (O-rings) |
| Tesnilo batnice | TPU (thermoplastic polyurethane) |
| Min. delovni tlak [bar] | 1.5 |
| Max. delovni tlak [bar] | 10 |
| Batnica Ø [mm] | 20 |
| Bat Ø [mm] | 50 |
| Max. temperaturno območje [°C] | 70 |
| Stroke [mm] | 500 |