**TRG d.o.o.**
**Celovška cesta 150, 1000 Ljubljana**

**Davčna št.:** SI 56119488
**Telefon:** 01 500 14 42
**E-mail:** info@podjetje-trg.si
**WWW:** www.www.karcher-trg.si

**Datum:** 10.11.2026



(slika je simbolična)

# stand. cilinderdelujoč v dveh smerehbat Ø 80hod 500G 3/8

Kategorija: Metalwork
Šifra: **106240RIE**

## Kratek opis

Standard cylinder, ISO 15552, double-acting, Piston Ø 80, Stroke 500, G 3/8, Working pressure max. 10 bar, Temp. -10 °C to 80 °C
These cylinders are ideal for a wide range of applications owing to their robust design and ecxellent value for money.
The standard type has a double-acting cylinder and features a magnetic piston as well as integrated cushioning.
The magnetic switches can be mounted in two T-slots on the same side as the compressed air supply.
The version with a 125 mm bore is provided with fixing accessories on three sides as standard.
Suitable for filtered, unlubricated or lubricated compressed air.
If lubrication is used, it must be continuous.

## Tehnične Specifikacije

| | |
|---|---|
| Min. temperaturno območje [°C] | -10 |
| Bat | Aluminium |
| Batnica | C45 steel, hard chrome-plated |
| Cushioning | cushioned |
| ET batnice | M20x1.5 |
| Ffunkcija | double-acting |
| Gewinde Kolbenstange | male piston rod |
| Magnet | with magnet |
| Navoj na batnici | M20x1.5 |
| Oblika | Heads / jacket with self-tapping screws |
| Ovoj | Anodised aluminium jacket with integrated T-slots |
| Povezava | G 3/8 |
| Standard | acc. to ISO 15552 |
| Tesnilo | NBR |
| Min. nastavljeni tlak [bar] | 0.2 |
| Max. delovni tlak [bar] | 10 |
| Batnica Ø [mm] | 25 |
| Bat Ø [mm] | 80 |
| Max. temperaturno območje [°C] | 80 |
| Stroke [mm] | 500 |