



(slika je simbolična)

stand. cilindrdelujoč v dveh smerehbat Ø 100hod 25G 1/2

Kategorija: [Metalwork](#)Šifra: **106243RIE**

Kratek opis

Standard cylinder, ISO 15552, double-acting, Piston Ø 100, Stroke 25, G 1/2, Working pressure max. 10 bar, Temp. -10 °C to 80 °C

These cylinders are ideal for a wide range of applications owing to their robust design and excellent value for money. The standard type has a double-acting cylinder and features a magnetic piston as well as integrated cushioning.

The magnetic switches can be mounted in two T-slots on the same side as the compressed air supply.

The version with a 125 mm bore is provided with fixing accessories on three sides as standard.

Suitable for filtered, unlubricated or lubricated compressed air.

If lubrication is used, it must be continuous.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Bat	Aluminium
Batnica	C45 steel, hard chrome-plated
Cushioning	cushioned
ET batnice	M20x1.5
Ffunkcija	double-acting
Gewinde Kolbenstange	male piston rod
Magnet	with magnet
Navoj na batnici	M20x1.5
Oblika	Heads / jacket with self-tapping screws
Ovoj	Anodised aluminium jacket with integrated T-slots
Povezava	G 1/2
Standard	acc. to ISO 15552
Tesnilo	NBR
Min. nastavljeni tlak [bar]	0.2
Max. delovni tlak [bar]	10
Batnica Ø [mm]	25
Stroke [mm]	25
Max. temperaturno območje [°C]	80
Bat Ø [mm]	100