



(slika je simbolična)

## stand. cilindodelujoč v dveh smerehbat Ø 63hod 160G 3/8

Kategorija: [Metalwork](#)Šifra: **106222RIE**

### Kratek opis

Standard cylinder, ISO 15552, double-acting, Piston Ø 63, Stroke 160, G 3/8, Working pressure max. 10 bar, Temp. -10 °C to 80 °C

These cylinders are ideal for a wide range of applications owing to their robust design and excellent value for money. The standard type has a double-acting cylinder and features a magnetic piston as well as integrated cushioning.

The magnetic switches can be mounted in two T-slots on the same side as the compressed air supply.

The version with a 125 mm bore is provided with fixing accessories on three sides as standard.

Suitable for filtered, unlubricated or lubricated compressed air.

If lubrication is used, it must be continuous.

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Bat	POM
Batnica	C45 steel, hard chrome-plated
Cushioning	cushioned
ET batnice	M16x1.5
Ffunkcija	double-acting
Gewinde Kolbenstange	male piston rod
Magnet	with magnet
Navoj na batnici	M16x1.5
Oblika	Heads / jacket with self-tapping screws
Ovoj	Anodised aluminium jacket with integrated T-slots
Povezava	G 3/8
Standard	acc. to ISO 15552
Tesnilo	NBR
Min. nastavljeni tlak [bar]	0.3
Max. delovni tlak [bar]	10
Batnica Ø [mm]	20
Bat Ø [mm]	63
Max. temperaturno območje [°C]	80
Stroke [mm]	160