



## Standardni manometer, CrNi jeklo, G 1/4, 0 - 16 bar, Ø 50

Kategorija: [Wika](#)  
Šifra: **102445RIE**

(slika je simbolična)

### Kratek opis

Standard pressure gauge CrNi steel design, Connection, rear, centric, G 1/4, Goods class 2.5, Measurement range 0 - 16 bar, Ø 50

Bourdon-tube pressure gauge (standard model) manufactured entirely from CrNi steel, economical and reliable.

Suitable for gaseous or liquid, corrosive and crystallising media which do not have high viscosity, also in corrosive atmosphere. Clean dry air applications, machinery and industrial plant engineering in general.

### Tehnične Specifikacije

|                                            |               |
|--------------------------------------------|---------------|
| Min. sobna temperatura [°C]                | -40           |
| Min. temperatura medija [°C]               | -40           |
| Material                                   | CrNi steel    |
| Material Prozessanschluss                  | CrNi steel    |
| Položaj povezave                           | rear, central |
| Povezava                                   | G 1/4         |
| Prednje steklo                             | Polycarbonate |
| Stopnja rasti na območju skale - bar [bar] | 0.5           |
| Razred točnosti                            | 2.5           |
| Merilno območje max. bar                   | 16            |
| Premjer [mm]                               | 50            |
| Max. sobna temperatura [°C]                | 60            |
| Max. temperatura medija [°C]               | 100           |
| Vrsta                                      | 131.11        |
| Merilno območje max. psi                   | 230           |