

Datum: 20.04.2026



(slika je simbolična)

Standardni manometer, sprednji obroč, G 1/4, 0 - 1.6 bar, Ø 50

Kategorija: [Wika](#)
Šifra: **101861RIE**

Kratek opis

Standard pressure gauge, front ring, Connection, rear, centric, G 1/4, Goods class 1.6, Measurement range 0 - 1.6 bar, Ø 50

Bourdon-tube pressure gauge in standard design, either with panel-mounting bezel made of chrome-plated or black sheet steel or

with 3-hole bezel made of chrome-plated sheet steel.

Suitable for gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Material Prozessanschluss	Copper alloy
Merilni element	Copper alloy
Ohišje	Sheet steel
Položaj povezave	rear, central
Povezava	G 1/4
Prednje steklo	Transparent plastic
Premikanje	Copper alloy
Spodnja/Zgornja meja območja	Positive pressure
Stopnja rasti na območju skale - bar [bar]	0.05
Merilno območje max. bar	1.6
Razred točnosti	1.6
Premer [mm]	50
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
Vrsta	111.12