



(slika je simbolična)

Standardni manometer, sprednji obroč, G 1/4, 0 - 6 bar, Ø 50

Kategorija: [Wika](#)
Šifra: **101864RIE**

Kratek opis

Standard pressure gauge, front ring, Connection, rear, centric, G 1/4, Goods class 1.6, Measurement range 0 - 6 bar, Ø 50
Bourdon-tube pressure gauge in standard design, either with panel-mounting bezel made of chrome-plated or black sheet steel or with 3-hole bezel made of chrome-plated sheet steel. Suitable for gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise.

Tehnične Specifikacije

| | |
|--|---------------------|
| Min. sobna temperatura [°C] | -20 |
| Min. temperatura medija [°C] | -20 |
| Material Prozessanschluss | Copper alloy |
| Merilni element | Copper alloy |
| Ohišje | Sheet steel |
| Položaj povezave | rear, central |
| Povezava | G 1/4 |
| Prednje steklo | Transparent plastic |
| Premikanje | Copper alloy |
| Spodnja/Zgornja meja območja | Positive pressure |
| Stopnja rasti na območju skale - bar [bar] | 0.2 |
| Razred točnosti | 1.6 |
| Merilno območje max. bar | 6 |
| Premer [mm] | 50 |
| Max. sobna temperatura [°C] | 60 |
| Max. temperatura medija [°C] | 60 |
| Vrsta | 111.12 |