

Datum: 01.07.2026



## Stropni nosilec s hN.N.rim priključkom I.D. 7.2G 1/2 N.N.

Kategorija: [Wall plate with quick disconnect coupling DN 7.2](#)  
Šifra: **107274RIE**

(slika je simbolična)

### Kratek opis

Ceiling bracket with quick-connect coupling I.D. 7.2, Bright brass, G 1/2 IT, Operating pressure 0-35 bar, Temp. -20 °C to 100 °C

1, 2 or 3-way distributor pieces made of brass with a bare metal surface, pre-assembled with quick disconnect coupling DN 7.2.

Available with threaded connection inside or outside or nipple for adaptation into an existing quick disconnect coupling DN 7.2 to DN 7.8.

### Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Ohišje	Brass with a bare metal surface
Povezava	G 1/2 IT
Spojke	DN 7.2, brass with a bare metal surface, G 1/2 ET
Tesnilo	Industrial adhesives, medium strength
Varovaka	Industrial adhesives, medium strength
Sestava distributerja	2 x G 1/2 IT
Max. obratovalni tlak [bar]	35
Premer [mm]	45.0
Višina [mm]	46.0
Max. sobna temperatura [°C]	100
Max. temperatura medija [°C]	100