



Stropni nosilec s hN.N.rim priključkom I.D. 7.2G 3/8 N.N.

Kategorija: [Wall plate with quick disconnect coupling DN 7.2](#)
Šifra: **107273RIE**

(slika je simbolična)

Kratek opis

Ceiling bracket with quick-connect coupling I.D. 7.2, Bright brass, G 3/8 IT, Operating pressure 0-35 bar, Temp. -20 °C to 100 °C

1, 2 or 3-way distributor pieces made of brass with a bare metal surface, pre-assembled with quick disconnect coupling DN 7.2.

Available with threaded connection inside or outside or nipple for adaptation into an existing quick disconnect coupling DN 7.2 to DN 7.8.

Tehnične Specifikacije

| | |
|------------------------------|---|
| Min. sobna temperatura [°C] | -20 |
| Min. temperatura medija [°C] | -20 |
| Ohišje | Brass with a bare metal surface |
| Povezava | G 3/8 IT |
| Spojke | DN 7.2, brass with a bare metal surface, G 3/8 ET |
| Tesnilo | Industrial adhesives, medium strength |
| Varovaka | Industrial adhesives, medium strength |
| Sestava distributerja | 2 x G 3/8 IT |
| Max. obratovalni tlak [bar] | 35 |
| Premer [mm] | 39.0 |
| Višina [mm] | 40.0 |
| Max. sobna temperatura [°C] | 100 |
| Max. temperatura medija [°C] | 100 |