

Datum: 02.05.2025

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

T-kos 130, 3 x Rp 1 1/4 N.N.črn

Kategorija: [Tee 130, female/female/female, black](#)
Šifra: **133675RIE**

Kratek opis

T-piece 130, 3 x Rp 1 1/4 IT, black malleable iron fitting,
Operating temp. -20 °C to 300 °C, ISO 7-1
According to DIN EN 10242 (previously 2950).
Malleable iron cast fittings in black steel, non-galvanized, is
the classic fitting series in connection series in piping
construction. Our malleable iron cast fittings are
characterized by high mechanical strength and standardized
fitting technology.
Working minimal temperature = -20 °C, 25 bar.
Working pressure for temperature range from -20 °C to 120
°C: 25 bar.
Working pressure for temperature range from 120 °C to 300
°C: 20-25 bar.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Material	Black malleable iron B350-10, design symbol A
Navoj	Rp 1 1/4
Površina	Black
Standardni navoj	acc. ISO 7-1
Max. temperaturno območje [°C]	300