

Datum: 24.05.2026



(slika je simbolična)

T-kos 130, N.N./N.N./N.N.Rp 1/2T-kos Rp 3/8

Kategorija: [Tee 130, reducing, female/female/female, black](#)
Šifra: **133678RIE**

Kratek opis

T-piece 130, IT/IT/IT, Rp 1/2, T-branch reducing Rp 3/8, black malleable iron fitting, Operating temp. -20 °C to 300 °C, ISO 7-1

According to DIN EN 10242 (previously 2950).

Malleable iron cast fittings in black steel, non-galvanized, is the classic fitting series in connection series in piping construction. Our malleable iron cast fittings are characterized by high mechanical strength and standardized fitting technology.

Working minimal temperature = -20 °C, 25 bar.

Working pressure for temperature range from -20 °C to 120 °C: 25 bar.

Working pressure for temperature range from 120 °C to 300 °C: 20-25 bar.

Tehnične Specifikacije

| | |
|--------------------------------|---|
| Min. temperaturno območje [°C] | -20 |
| Material | Black malleable iron B350-10, design symbol A |
| Navoj 1 | Rp 1/2 |
| Navoj 2 Zmanjšana razvejanost | Rp 3/8 |
| Navoj 3 | Rp 1/2 |
| Površina | Black |
| Standardni navoj | acc. ISO 7-1 |
| Max. temperaturno območje [°C] | 300 |