

Datum: 31.05.2026

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si

T-kos 130, N.N./N.N./N.N.Rp 1/2T-kos Rp 1/4

Kategorija: [Tee 130, reducing, female/female/female](#)
Šifra: **112970RIE**

(slika je simbolična)

Kratek opis

T-piece 130, IT/IT/IT, Rp 1/2, T-branch reducing Rp 1/4,
Operating temp. -20°C to 300°C, black malleable cast iron,
Hot-dip galva.

Acc. to DIN EN 10242 (formerly DIN 2950)
The classic - and the most popular - screw fitting series for
pipe construction.
These fittings are characterized by their high mechanical
strength and surface quality to DIN 2444.
They are completely coated with a layer of pure zinc and are
therefore suitable for drinking water

Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Material	Black malleable iron B350-10, design symbol A
Navoj 1	Rp 1/2
Navoj 2 Zmanjšana razvejanost	Rp 1/4
Navoj 3	Rp 1/2
Površina	Hot dip galvanised
Standardni navoj	acc. ISO 7-1
Max. temperaturno območje [°C]	300